REGEIVED CENTRAL FAX CENTED

FULL VERSION OF ALL PENDING CLAIMS DEC 0 1 2006

- 1. (Currently Amended) A liquid crystal display apparatus, comprising: a first panel including:
 - a first transparent substrate having a pixel area;
- a thin film transistor disposed at the pixel area so as to output a pixel voltage;
- a <u>first</u> color filter disposed at the pixel area, the first color filter having a first edge;
- a second color filter disposed adjacent to the first color filter and having a second edge, the first edge and the second edge being overlapped to provide an overlapped area between the first color filter and the second color filter;
- a spacer disposed on [[an]] the overlapped area between the <u>first</u> color filter and [[an]] the adjacent <u>second</u> color filter, the spacer having a same material as <u>one</u> of the <u>first</u> color filter and the second color filter; and
- a pixel electrode disposed on the <u>first</u> color filter so as to receive the pixel voltage;
 - a second panel including:
 - a second transparent substrate; and
 - a common electrode disposed on the second transparent substrate; and a liquid crystal layer disposed between the first and second panels.
- 2. (Currently Amended) The liquid crystal display apparatus of claim 1, wherein the <u>first</u> color filter comprises a red color filter, a green color filter and a blue color filter, and the spacer comprises at least one of a red color filter, a green color filter and a blue color filter.
- 3. (Currently Amended) The liquid crystal display apparatus of claim 1, wherein the second panel further comprises a light blocking pattern having a lattice-shape, which is disposed on the common electrode, the light blocking pattern that transmits light incident into the pixel area and blocks light incident into between the pixel area and [[the]] an adjacent pixel area.

LAW OFFICES OF
MACPHERSON KWOX CHEN &
HEID LLD

2403 MICHELSON DRIVE
SWIT 210

IRVING CA 92612
(949) 727-7040
PAX (409) 392-3223

Page 5 of 16

- 4. (Previously presented) The liquid crystal display apparatus of claim 3, wherein the liquid crystal layer comprises liquid crystal molecules vertically aligned, and the second panel further comprises a light visual angle pattern disposed on the common electrode and formed at a position corresponding to the pixel area so as to widen a visual angle of an image.
- 5. (Currently Amended) The liquid crystal display apparatus of claim 1, wherein the second panel further comprises a light blocking pattern having a lattice-shape, which is disposed between the second transparent substrate and common electrode and formed at a position corresponding to a space between the pixel area and adjacent pixel area, so as to block light incident into between the pixel area and [[the]] an adjacent pixel area.
- 6. (Previously presented) The liquid crystal display apparatus of claim 5, wherein the liquid crystal layer comprises liquid crystal molecules vertically aligned, and the second panel further comprises a light visual angle pattern disposed between the second transparent substrate and common electrode and formed at the position corresponding to the pixel area so as to widen a visual angle of an image.
- 7. (Currently Amended) The liquid crystal display apparatus of claim 1, wherein the second panel further comprises:
- a light blocking pattern having a lattice-shape, which is disposed on the common electrode and formed at a position corresponding to a space between the pixel area and adjacent pixel area, so as to block light incident into between the pixel area and [[the]] an adjacent pixel area; and
 - a photosensitive pattern disposed on the light blocking pattern.
- 8. (Previously presented) The liquid crystal display apparatus of claim 7, wherein the liquid crystal layer comprises liquid crystal molecules vertically aligned, and the second panel further comprises a first light visual angle pattern disposed on the common electrode and formed at a position corresponding to the pixel area so as to widen a visual angle of an image and a second light visual angle pattern disposed on the first light visual angle pattern.

LAW OFFICES OP MACHIBESON KYOK CHEN (MEID L., 2402 MICHELSON DRIVE SUITE 210 IRVINE CA 92412 (949) 152-7010

Page 6 of 16

- 9. (Currently Amended) The liquid crystal display apparatus of claim 1, wherein the second panel further comprises:
- a light blocking pattern having a lattice-shape, which is disposed between the second transparent substrate and common electrode and formed at a position corresponding to a space between the pixel area and <u>an</u> adjacent pixel area, the light blocking pattern that transmits light incident into the pixel area and blocks light incident into between the pixel area and the adjacent pixel area; and
 - a photosensitive pattern disposed on the light blocking pattern.
- 10. (Previously presented) The liquid crystal display apparatus of claim 9, wherein the liquid crystal layer comprises liquid crystal molecules vertically aligned, and the second panel further comprises a first light visual angle pattern disposed between the first transparent substrate and common electrode and formed at a position corresponding to the pixel area so as to widen a visual angle of an image and a second light visual angle pattern disposed on the first light visual angle pattern.
- 11. (Currently Amended) The liquid crystal display apparatus of claim 1, wherein the liquid crystal layer comprises liquid crystal molecules vertically aligned, and wherein the second panel further comprises:
- a light blocking pattern having a lattice-shape, which is disposed between the second transparent substrate and common electrode so as to transmit light incident into the pixel area and block light incident into between the pixel area and [[the]]an adjacent pixel area; and
- a light visual angle pattern disposed on common electrode and formed at a position corresponding to the pixel area so as to widen a visual angle of an image.
- 12. (Previously presented) The liquid crystal display apparatus of claim 11, wherein the second panel further comprises a transparent spacer disposed on the common electrode corresponding to the light blocking pattern.
- 13. (Previously presented) The liquid crystal display apparatus of claim 1, wherein the second panel further comprises a light visual angle pattern disposed on the

LAW OFFICES OF MACMIERSON KWOK CHEN & HEID JLP 2403 MICHELSON DRIVE SUITE 210 IRVINE CA 92612 (949) 752-7040 PAX (490 792-9262

Page 7 of 16

common electrode corresponding to the pixel area so as to widen a visual angle of an image.

- 14. (Previously presented) The liquid crystal display apparatus of claim 13, wherein the second panel further comprises a transparent spacer disposed on the common electrode corresponding to the spacer.
- 15. (Previously presented) The liquid crystal display apparatus of claim 1, wherein the liquid crystal layer comprises liquid crystal molecules vertically aligned, and the second panel further comprises a light visual angle pattern disposed between the common electrode and second transparent substrate and formed at a position corresponding to the pixel area so as to widen a visual angle of an image.
- 16. (Previously presented) The liquid crystal display apparatus of claim 15, wherein the second panel further comprises a transparent spacer disposed between the common electrode and second transparent substrate and formed at a position corresponding to the spacer.
- 17. (Withdrawn) A method of manufacturing a liquid crystal display apparatus, comprising:

forming a first substrate including:

forming a pixel voltage applying part so as to output a pixel voltage to each pixel area of a first transparent substrate;

forming a color filter and a color filter spacer having a same material as the color filter, the color filter corresponding to the pixel area and the color filter spacer being formed at a position corresponding to a space between the pixel area and an adjacent pixel area; and

forming a pixel electrode on the color filter to form a first substrate, the pixel electrode receiving the pixel voltage;

forming a common electrode, which is facing the pixel electrode, on a second transparent substrate to form a second substrate, the second transparent substrate combining with the first transparent substrate; and

disposing liquid crystal between the first and second substrates.

Page 8 of 16

Appl. No. 10/719,103

LAW OFFICES OF BLACHIBRSON KWOK CUEN & IRID 11P 2402 MICHELSON DRIVE SUITE 210 12VING CA 92612 (949) 723-740 FAK (468) 333-7362 18. (Withdrawn) The method of claim 17, wherein the color filter and color filter spacer are formed by:

forming a red color filter layer on the second transparent substrate;

patterning the red color filter layer to form a red color filter at an nth pixel area,
where n is a natural number, and a red color filter spacer between the pixel area and the
adjacent pixel area;

forming a green color filter layer on the second transparent substrate; patterning the green color filter layer to form a green color filter at an (n+1)th pixel area and a green color filter spacer on the red color filter spacer;

forming a blue color filter layer on the second transparent substrate; and patterning the blue color filter layer to form a blue color filter at an (n+2)th pixel area and a blue color filter spacer on the green color filter spacer.

19. (Withdrawn) The method of claim 17, prior to forming the common electrode, further comprising:

forming a light blocking layer on the second transparent substrate; and patterning the light blocking layer to form a light blocking pattern having a lattice-shape, the light blocking pattern transmitting light incident into the pixel area and blocking light incident into between the pixel area and adjacent pixel area.

- 20. (Withdrawn) The method of claim 19, wherein a light visual angle pattern is further formed on the second transparent substrate so as to widen a visual angle of an image while the light blocking layer is pattern.
- 21. (Withdrawn) The method of claim 17, prior to forming the common electrode, further comprising:

forming a light blocking layer on the second transparent substrate;
forming a transparent organic layer on the light blocking layer;
patterning the transparent organic layer to form a transparent spacer facing the
color filter spacer; and

patterning the light blocking layer to form a light blocking pattern under the transparent spacer.

LAW OFFICES OF NACPHERSON KWOK CHEN A HUB LLT 2403 MICHELSON DRIVE SUITE 210 10 VINE CA 02x12 (949) 152-7040 FAX (903) 152-9252

Page 9 of 16

- 22. (Withdrawn) The method of claim 21, wherein a light visual angle pattern is further formed on the second transparent substrate corresponding to the pixel area so as to widen a visual angle of an image while the light blocking layer is pattern.
- 23. (Withdrawn) The method of claim 17, prior to forming the common electrode, further comprising:

forming a light blocking layer on the second transparent substrate;
forming a photosensitive layer on the light blocking layer; and
patterning the photosensitive layer to form a first photosensitive pattern having a
lattice-shape, the first photosensitive pattern transmitting light incident into the pixel area
and blocking light incident into between the pixel area and adjacent pixel area; and

patterning the light blocking layer using the first photosensitive pattern as a mask to form a light blocking pattern under the first photosensitive pattern.

24. (Withdrawn) The method of claim 23, wherein the first photosensitive pattern is formed by:

patterning the photosensitive layer formed at a position facing the pixel area to form a second photosensitive pattern; and

patterning the light blocking layer using the second photosensitive pattern as a mask to form a light visual angle pattern.

25. (Withdrawn) The method of claim 17, after forming the common electrode, further comprising:

forming a light blocking layer on the common electrode; and patterning the light blocking layer to form a light blocking pattern having a lattice-shape, the light blocking pattern transmitting light incident into the pixel area and blocking light incident into between the pixel area and adjacent pixel are.

26. (Withdrawn) The method of claim 25, wherein a light visual angle pattern is further formed on the common electrode corresponding to the pixel area so as to widen a visual angle of an image while the light blocking layer is pattern.

LAW OFFICES OF PIACPHERSON KWOK CHEN & HEID LLP 2403 MICHELSON DRIVE SUITE 210 IRVINE CA 92612 (249) 752-7040 PAK (488) 322-2652

Page 10 of 16

27. (Withdrawn) The method of claim 25, after forming the common electrode, further comprising:

forming a transparent organic layer on the common electrode; and patterning the transparent organic layer to form a transparent spacer at the light blocking pattern facing the color filter spacer.

- 28. (Withdrawn) The method of claim 27, wherein the pattern of the transparent organic layer further comprises forming a light visual angle pattern at a position facing the pixel area by patterning the transparent organic layer.
- 29. (Withdrawn) The method of claim 17, after forming the common electrode, further comprising:

forming a light blocking layer on the second transparent substrate;
forming a photosensitive layer on the light blocking layer; and
patterning the photosensitive layer to form a first photosensitive pattern having a
lattice-shape, the first photosensitive pattern transmitting light incident into the pixel area
and blocking light incident into between the pixel area and adjacent pixel area; and

patterning the light blocking layer using the first photosensitive pattern as a mask to form a light blocking pattern.

30. (Withdrawn) The method of claim 29, wherein the first photosensitive pattern is formed by:

patterning the photosensitive layer formed at a position facing the pixel area to form a second photosensitive pattern; and

patterning the light blocking layer using the second photosensitive pattern as a mask to form a light visual angle pattern.

- 31. (Previously Presented) The liquid crystal display apparatus of claim 1, wherein the spacer has a column shape, the spacer being configured to maintain a cell gap between the first substrate and the second substrate.
- 32. (Previously Presented) The liquid crystal display apparatus of claim 1, wherein the common electrode makes direct contact with the spacer.

Law Oppices op (acplerson Kwok Chen & Med Lip 2402 Mechblson Drive Suite 210 Irvine Ca 92612 (349) 752-7040 Pax (408) 792-0222

Page 11 of 16